


# Aerial Work Platforms

## IWP™ Super Series™

### Specifications



| Models                         | IWP-20S    |        | IWP-25S    |        | IWP-30S    |        |
|--------------------------------|------------|--------|------------|--------|------------|--------|
| Measurements                   | US         | Metric | US         | Metric | US         | Metric |
| Working height*                | 26 ft 2 in | 8.15 m | 30 ft 5 in | 9.44 m | 35 ft 6 in | 11 m   |
| Platform height                | 20 ft 2 in | 6.15 m | 24 ft 5 in | 7.44 m | 29 ft 6 in | 9 m    |
| <b>A</b> Horizontal outreach** | 2 ft 2 in  | 0.66 m | —          | —      | —          | —      |
| <b>B</b> Height - stowed:      |            |        |            |        |            |        |
| fully lowered                  | 6 ft 4 in  | 1.93 m | 6 ft 4 in  | 1.93 m | 6 ft 4 in  | 1.93 m |
| base raised                    | 6 ft 6 in  | 1.98 m | 6 ft 6 in  | 1.98 m | 6 ft 6 in  | 1.98 m |
| <b>C</b> Length                | 5 ft       | 1.52 m | 5 ft       | 1.52 m | 5 ft       | 1.52 m |
| <b>D</b> Width - standard base | 2 ft 8 in  | 0.81 m | 2 ft 8 in  | 0.81 m | —          | —      |
| wide base                      | —          | —      | —          | —      | 3 ft 4 in  | 1.02 m |
| Corner access***               | 6 in       | 0.15 m | 6 in       | 0.15 m | 7 in       | 0.18 m |

### Productivity

|                              |                 |              |                 |              |                 |              |
|------------------------------|-----------------|--------------|-----------------|--------------|-----------------|--------------|
| Lift capacity: ANSI/CE/CSA   | 350 lbs         | 159 kg       | 350 lbs         | 159 kg       | 350 lbs         | 159 kg       |
| ANSI/CE with outreach option | 300 lbs         | 136 kg       | —               | —            | —               | —            |
| Platform Dimensions (l/w/h)  |                 |              |                 |              |                 |              |
| Standard                     | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm |
| Gated standard               | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm | 27/26/44.75 in  | 69/66/114 cm |
| Gated narrow                 | 26/20/44.75 in  | 66/51/114 cm | 26/20/44.75 in  | 66/51/114 cm | 26/20/44.75 in  | 66/51/114 cm |
| Standard fiberglass**        | 29/26.5/43.5 in | 74/67/110 cm | 29/26.5/43.5 in | 74/67/110 cm | 29/26.5/43.5 in | 74/67/110 cm |

### Power

|           |   |
|-----------|---|
| AC models | 110 V / 50-60 Hz or 220 V / 50-60 Hz              |
| DC models | 12V / 110 V / 60 Hz or 110/230 Hz worldwide model |

### Weight\*\*\*\*

#### Standard base

|               |           |        |           |        |   |   |
|---------------|-----------|--------|-----------|--------|---|---|
| ANSI (AC)/CSA | 1,245 lbs | 565 kg | 1,290 lbs | 585 kg | — | — |
| ANSI (DC)/CSA | 1,345 lbs | 610 kg | 1,390 lbs | 630 kg | — | — |
| CE (AC)       | 1,245 lbs | 565 kg | 1,290 lbs | 585 kg | — | — |
| CE (DC)       | 1,345 lbs | 610 kg | 1,390 lbs | 630 kg | — | — |

#### Standard base with outreach option

|           |           |        |   |   |   |   |
|-----------|-----------|--------|---|---|---|---|
| ANSI (AC) | 1,350 lbs | 612 kg | — | — | — | — |
| ANSI (DC) | 1,450 lbs | 658 kg | — | — | — | — |
| CE (AC)   | 1,350 lbs | 612 kg | — | — | — | — |
| CE (DC)   | 1,450 lbs | 658 kg | — | — | — | — |

#### Wide base

|               |   |   |   |   |           |        |
|---------------|---|---|---|---|-----------|--------|
| ANSI (AC)/CSA | — | — | — | — | 1,430 lbs | 649 kg |
| ANSI (DC)/CSA | — | — | — | — | 1,530 lbs | 694 kg |
| CE (AC)       | — | — | — | — | 1,430 lbs | 649 kg |
| CE (DC)       | — | — | — | — | 1,530 lbs | 694 kg |

### Standards Compliance

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Fiberglass platforms are not available with the outreach option.

\*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

\*\*\*\* Weight will vary depending on options and/or country standards.

### Features

#### Standard Features

##### Measurements

###### IWP-20S

- 26 ft 6 in (8.24 m) working height
- 20 ft 2 in (6.15 m) platform height
- 2 ft 8 in (0.81 m) standard base width
- Outreach option adds 2 ft 2 in (0.66 m) of horizontal reach
- Up to 350 lbs (159 kg) lift capacity

###### IWP-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- Up to 350 lbs (159 kg) lift capacity

###### IWP-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lbs (159 kg) lift capacity

##### Productivity

- Standard base (IWP™-20S and 25S only)
- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupter lower receptacle
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

##### Power

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system

#### Options & Accessories

##### Productivity

- Outreach option (IWP-20S only)
- Operational warning light and descent alarm package (mandatory for CE and AUS)
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

##### Power

- Power wheel assist with dual battery package\*
- Dual battery package
- DC power 85V, 110V or 220V / 50-60 Hz

##### Platform

- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform

##### Base

- Wide base (IWP™-30 only)

\* Adds 12.5 in (.32 m) to unit length and 285 lbs (129 kg) to unit weight



#### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

#### Genie Europe

The Maltings  
Wharf Road  
Grantham NG31 6BH  
UK  
Telephone +44 (0)1476 584333  
Fax +44 (0)1476 584334  
Email: AWP-InfoEurope@terex.com

#### Distributed By:

Effective Date: May, 2013. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2013 Terex Corporation.